

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 January 2002 (24.01.2002)

PCT

(10) International Publication Number
WO 02/007481 A3

(51) International Patent Classification⁷: **H04S 3/02**

(21) International Application Number: **PCT/EP01/07757**

(22) International Filing Date: **5 July 2001 (05.07.2001)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
00202588.0 19 July 2000 (19.07.2000) EP

(71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]**; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors: **IRWAN, Roy**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **AARTS, Ronaldus, M.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **SCHOENMAKER, Maarten**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): CN, JP, KR.

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
19 December 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **MULTI-CHANNEL STEREO CONVERTER FOR DERIVING A STEREO SURROUND AND/OR AUDIO CENTRE SIGNAL**



(57) **Abstract:** A multi-channel stereo converter is described comprising stereo magnitude determining means for generating a stereo information signal (a/b; (p), which represents a degree of stereo between audio input signals (L, R), and transforming means for transforming said audio signals (L, R) based on said stereo information signal (a/b; (p) into at least a surround signal (S). A space mapping interpretation is presented and an audio centre signal may be derived from the stereo input signals as well. The result is more flexibility in application and design, without substantial cross talk in the audio signals.